



## **ADDENDUM NO. 1 - OUTLINE AND SUMMARY INFORMATION**

Project Name: Bobcat Stadium East Painting

PPA No.: 19-0081

Date: May 23, 2019

---

To: *All Plan Holders of Record*

*The Plans and Specification prepared by Campus Planning Design and Construction dated May 10, 2019, shall be clarified and added as follow. The bidder proposes to perform all the following clarifications or changes. It is understood that the Base Bid shall include any modification of Work or Additional Work that may be required by reason of the following change or clarifications.*

*The Bidders are to acknowledge the receipt of this Addendum by inserting its number and date into their Bid Forms. Failure to acknowledge may subject the Bidder to disqualification and rejection of the bid. This Addendum forms part of the Contract Documents as if bound therein and modifies them as follows:*

### **I. AMENDMENTS TO THE PROJECT MANUAL**

- A. The contractor shall sprinkle PPG Amercoat 888, anti-skid additive, on the wet primed horizontal walking surfaces following the manufacturer's instructions for application. The sealer coat will be applied onto these surfaces.

### **II. AMENDMENTS TO THE DRAWINGS**

- B. The contractor will not be responsible for applying new adhesive tier numbers at the stair risers. This work will be performed by MSU's technical staff.
- C. The contractor will not be responsible for applying new adhesive warning strips at the stair treads. This work will be performed by MSU's technical staff.

### **III. ATTACHMENTS**

- A. PPG 888 (Amercoat 888) anti-skid additive product data sheet.

END OF ADDENDUM NO. 1

# PPG 888 (AMERCOAT® 888) ANTI-SKID ADDITIVE

## DESCRIPTION

Aluminum oxide non-skid aggregate

## PRINCIPAL CHARACTERISTICS

- Hard aluminum oxide aggregate with excellent abrasion resistance
- Suitable for marine and offshore for main decks, helidecks, walkways and other areas with heavy traffic
- Suitable for use in combination with flooring products
- Provides a heavy non-skid surface
- Blend of 16 and 36 mesh aluminum oxide (average 24 mesh - 0.7 mm)

## COLOR AND GLOSS LEVEL

- Aluminum gray

## BASIC DATA

Data for mixed product	
Number of components	One
Shelf life	At least 60 months when stored cool and dry

## INSTRUCTIONS FOR USE

- Add to mixed units of AMERLOCK 2/400GF or broadcast into the applied film
- Add slowly to products under mechanical agitation
- Mix frequently to avoid settling
- Apply with a mastic spray gun or a short nap roller
- Alternatively, sprinkle (openly or fully) into wet film of the epoxy or flooring product
- A layer of sealer or more durable topcoat can be applied on top of the anti-skid layer for a better aesthetic appearance and a more moderate profile
- Refer to the PDS of the specific flooring product for more detailed information on application

## WORLDWIDE AVAILABILITY

It is always the aim of PPG Protective and Marine Coatings to supply the same product on a worldwide basis. However, slight modification of the product is sometimes necessary to comply with local or national rules/circumstances. Under these circumstances an alternative product data sheet is used.

## REFERENCES

- |                                      |                   |      |
|--------------------------------------|-------------------|------|
| • CONVERSION TABLES                  | INFORMATION SHEET | 1410 |
| • EXPLANATION TO PRODUCT DATA SHEETS | INFORMATION SHEET | 1411 |



# PPG 888 (AMERCOAT® 888) ANTI-SKID ADDITIVE

## WARRANTY

PPG warrants (i) its title to the product, (ii) that the quality of the product conforms to PPG's specifications for such product in effect at the time of manufacture and (iii) that the product shall be delivered free of the rightful claim of any third person for infringement of any U.S. patent covering the product. THESE ARE THE ONLY WARRANTIES THAT PPG MAKES AND ALL OTHER EXPRESS OR IMPLIED WARRANTIES, UNDER STATUTE OR ARISING OTHERWISE IN LAW, FROM A COURSE OF DEALING OR USAGE OF TRADE, INCLUDING WITHOUT LIMITATION, ANY OTHER WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR USE, ARE DISCLAIMED BY PPG. Any claim under this warranty must be made by Buyer to PPG in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life of the product, or one year from the date of the delivery of the product to the Buyer, whichever is earlier. Buyer's failure to notify PPG of such non-conformance as required herein shall bar Buyer from recovery under this warranty.

---

## LIMITATIONS OF LIABILITY

IN NO EVENT WILL PPG BE LIABLE UNDER ANY THEORY OF RECOVERY (WHETHER BASED ON NEGLIGENCE OF ANY KIND, STRICT LIABILITY OR TORT) FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES IN ANY WAY RELATED TO, ARISING FROM, OR RESULTING FROM ANY USE MADE OF THE PRODUCT. The information in this sheet is intended for guidance only and is based upon laboratory tests that PPG believes to be reliable. PPG may modify the information contained herein at any time as a result of practical experience and continuous product development. All recommendations or suggestions relating to the use of the PPG product, whether in technical documentation, or in response to a specific inquiry, or otherwise, are based on data, which to the best of PPG's knowledge, is reliable. The product and related information is designed for users having the requisite knowledge and industrial skills in the industry and it is the end-user's responsibility to determine the suitability of the product for its own particular use and it shall be deemed that Buyer has done so, as its sole discretion and risk. PPG has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Therefore, PPG does not accept any liability arising from any loss, injury or damage resulting from such use or the contents of this information (unless there are written agreements stating otherwise). Variations in the application environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results. This sheet supersedes all previous versions and it is the Buyer's responsibility to ensure that this information is current prior to using the product. Current sheets for all PPG Protective & Marine Coatings Products are maintained at [www.ppgpmc.com](http://www.ppgpmc.com). The English text of this sheet shall prevail over any translation thereof.

The PPG logo, and all other PPG marks are property of the PPG group of companies. All other third-party marks are property of their respective owners.

