CAMPUS FIRE HYDRANT UPGRADES

WATER SYSTEM IMPROVEMENTS

PROJECT LOCATION: BOUNDED TO THE NORTH BY WEST COLLEGE STREET, TO THE EAST BY SOUTH 5TH AVE, TO THE

SOUTH BY WEST KAGY AVE. AND WEST BY SOUTH 19TH AVE IN THE CITY OF BOZEMAN. MONTANA.

LEGAL DESCRIPTION: LOCATED IN SECTION 13, TOWNSHIP 02S, RANGE 05E, P.M.M., GALLATIN COUNTY, MT

NOVEMBER 17, 2023

MONTANA STATE UNIVERSITY - BOZEMAN OWNER:

UNIVERSITY FACILITIES MANAGEMENT

PO BOX 172760

BOZEMAN, MT 59717-2760 PHONE: 406-997-2001

ALLIED ENGINEERING SERVICES, INC. **CIVIL ENGINEER:**

32 DISCOVERY DRIVE BOZEMAN, MT 59718



SHEET INDEX

SHEET NO.										
C0.1	COVER									
C0.2	PROJECT NOTES & GENERAL INFORMATION									
C0.3	EXISTING HYDRANT SUMMARY & NOTES									
C1.1	PROJECT OVERVIEW PLAN									
C2.1	PLAN & PROFILES HYDRANTS 72, 73, 68									
C2.2	PLAN & PROFILES HYDRANTS 65, 64, 63									
C2.3	PLAN & PROFILES HYDRANTS 59, 55, 56									
C2.4	PLAN & PROFILES HYDRANTS 61, 58, 62									
C2.5	PLAN & PROFILES HYDRANTS 13, 22, 53									
C2.6	PLAN & PROFILE HYDRANT 27									
C3.1	ISOLATION PLAN: HYDRANTS 55, 56, 58, 59, 61, 62, 63, 64, 65									
C3.2	ISOLATION PLAN: HYDRANTS 68, 72, 73									
C3.3	ISOLATION PLAN: HYDRANTS 22, 27, 53									
C3.4	ISOLATION PLAN: HYDRANT 13									
C4.1	DETAILS									
C4.2	DETAILS									

PROJECT ENGINEER: RORY S. ROMEY, PE

ERIC FOSS, EI **DESIGN ENGINEER:**


PROJECT SURVEYORS: GREG FINCK, PLS


> BRANDON SCHREINER, PLS CONNER SWITZER, EI DAX GROSSMAN











MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413 FAX: 406.994.5665

DE

PGRA FIRE S

PRELIMINARY - NOT FOR CONSTRUCTION CAMPU



DRAWN BY: REVIEWED BY RSR REV. DESCRIPTION DATE



PPA#22-0574 A/E#00-00-00 **AESI # 22-133**

SHEET TITLE CO.1

SHEET

COVER

LEGEND

INDEX CONTOUR - EG (5' INTERVAL) CONTOUR MINOR - FG (1' INTERVAL) — OHP — OVERHEAD POWER — EXISTING — G —— UG GAS (FROM UTILITY LOCATE PAINT) — EX. TEL UG PHONE (FROM UTILITY LOCATE PAINT) - EX. - E - UG ELECTRIC (FROM UTILITY LOCATE PAINT) - EX. ---- F ---- UG FIBER (FROM UTILITY LOCATE PAINT) - EX. - - ROAD CENTERLINE - EXISTING EDGE OF PAVEMENT - EXISTING CURB FLOWLINE - EXISTING TOP BACK OF CURB - EXISTING EDGE OF CONCRETE - EXISTING

- FENCE - EXISTING

BUILDING - EXISTING

SEWER MAIN (FROM UTILITY LOCATE PAINT) - EX ANTICIPATED EX. SEWER MAIN PER MSU RECORD DWGS —ss——ss——ss—— ANTICIPATED EX. SEWER SERVICE PER MSU RECORD DWGS WATER MAIN (FROM UTILITY LOCATE PAINT) - EX. ANTICIPATED EX. WATER MAIN PER MSU RECORD DWGS -ws-ws-ws-ws- ANTICIPATED EX. WATER SERVICE PER MSU RECORD DWGS STORM DRAIN (FROM UTILITY LOCATE PAINT) - EX. FIRE HYDRANT - EXISTING FIRE HYDRANT - PROPOSED WATER VALVE/HYDRANT AUX VALVE - EX.

ELECTRICAL PEDESTAL - EXISTING ELEC ELECTRICAL BOX - EXISTING TELEPHONE PEDESTAL - EXISTING

ANTICIPATED EX. WATER VALVE PER MSU RECORD DWGS

STORM DRAIN CURB INLET - EX. STORM DRAIN COMB. CURB INLET - EX. GAS VALVE - EXISTING SIGN - EXISTING TREE CONIFER - EXISTING TREE CONIFER - EXISTING

SANITARY SEWER MANHOLE - EX

STORM DRAIN MANHOLE - EX.

ICV IRRIGATION CONTROL VALVE - EX. LIGHT POLE - EXISTING Ε

(S)

SATELLITE DISH - EXISTING

CONTROL POINT

STORM DRAIN GRATE INLET - EX.

₩V

WEST GARFIELD ST

MONTANA STATE UNIVERSITY OWNED PARCELS PER 12/2/2022 CADASTRAL (GALLATIN COUNTY) SHAPEFILE (TYP.) BOUNDARIES ARE VERY APPROXÌMATÉ

GENERAL SPECIFICATIONS & NOTES:

ALL CONSTRUCTION WILL CONFORM TO THE MONTANA PUBLIC WORKS STANDARD SPECIFICATIONS (MPWSS), SEVENTH EDITION, AND THE CITY OF BOZEMAN (COB) MODIFICATIONS TO MPWSS AND THE PROJECT

 CONTRACTOR SHALL FIELD—VERIFY LINE AND GRADE OF EXISTING
CONNECTIONS. CONTRACTOR MUST NOTIFY ENGINEER IF EXISTING CONNECTION LOCATIONS AND ELEVATIONS ARE DIFFERENT THAN THOSE

3. ANY EXISTING OR NEW VALVES WHICH CONTROL THE COB's WATER SUPPLY OR MSU WATER SYSTEM SHALL BE OPERATED BY COB PERSONNEL ONLY OR MSU PERSONNEL ONLY, RESPECTIVELY.

4. THE CONTRACTOR SHALL NOTIFY THE WATER DEPARTMENT A MINIMUM OF 24-HOURS PRIOR TO BEGINNING ANY WORK.

CONSTRUCTION INSPECTION AND TESTING MUST BE PERFORMED BY A PROFESSIONAL ENGINEER LICENSED IN THE STATE OF MONTANA. THE ENGINEER SHALL BE NOTHED AT LEAST TWO DAYS PRIOR TO ANY WORK COMMENCING. THE CONTRACTOR AND THE ENGINEER WILL NEED TO COMMUNICATE DAILY SUCH THAT ALL CONSTRUCTION INSPECTION AND TESTING REQUIREMENTS CAN BE CORDINATED. INSPECTION AND TESTING SHALL MEET MPWSS, MDEQ, AND COB REQUIREMENTS.

THE CONTRACTOR IS REQUIRED TO CALL THE NATIONAL ONE CALL NUMBER FOR UTILITY LOCATES. NOT ALL EXISTING UTILITIES MAY BE SHOWN ON THE PLANS AND/OR THE DEPICTED LOCATIONS MAY NOT REPRESENT ACTUAL FIELD CONDITIONS. THEREFORE, THE CONTRACTOR SHALL ONLY USE THE UTILITY INFORMATION THAT IS SHOWN ON THE PLANS AS A GENERAL GUIDELINE AND MUST NOT DEPEND ON ITS ACCURACY. PRIOR TO PERFORMING ANY EXCAVATION, A UTILITY REQUEST SHALL BE MADE AND ALL UTILITIES SHALL BE MARKED BY THE UTILITY LOCATING COMPANY. THE CONTRACTOR IS RESPONSIBLE FOR GIVING THIS NOTICE BY CALLING (ROD) 424-5555 (DO CALL BILL) AT LEAST 2 BLISINESS DAYS PRIOR TO THE CONTRACTOR IS RESPONSIBLE FOR GIVING THIS NOTICE BY CALLING (800) 424—5555 (OR CALL BIT) AT LEAST 2 BUSINESS DAYS PRIOR TO ANY EXCAVATION. UNDERGROUND UTILITIES MUST BE FLAGGED OFF BEFORE ANY EXCAVATION CAN BEGIN. THE ENGINEER HAS NOT PHYSICALLY LOCATED OR FIELD VERIFIED ANY OF THE UNDERGROUND UTILITY LOCATIONS AND THEREFORE IS NOT RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF THE PLAN INFORMATION.

CONTRACTOR SHALL FIELD VERIFY LOCATION AND DEPTH OF ALL EXISTING UTILITIES WHERE NEW FACILITIES CROSS OR CONNECT. CONTRACTOR SHALL BE RESPONSIBLE FOR EXPOSING POTENTIAL UTILITY CONFLICTS FAR ENOUGH AHEAD OF CONSTRUCTION TO MAKE NECESSARY MODIFICATIONS WITHOUT DELAYING THE WORK. ALL UTILITY CROSSINGS SHALL BE POTHOLED AS NECESSARY PRIOR TO EXCAVATING OR BORNING TO ALLOW THE CONTRACTOR TO REPORT CRADE OF ALCOMENT CONDETICES. TO PREVENT GRADE OR ALIGNMENT CONFLICTS.

8. ALL ELEVATIONS SHOWN ARE IN DECIMAL FEET. MOST DIMENSIONS ARE SHOWN IN DECIMAL FEET AND OCCASIONALLY SHOWN IN INCHES.

PIPE BEDDING (TYPE 1) AND TRENCH BACKFILL (SEE CITY OF BOZEMAN STANDARD DRAWINGS # 02221-1 AND # 02221-2) SHALL BE UTILIZED IN ACCORDANCE WITH MPWSS SECTIONS 02221, 02225, 02234, 02235, 02510 AND THE ASSOCIATED STANDARD DRAWINGS AND THE ASSOCIATED COB MODIFICATIONS TO MPWSS, UNLESS NOTED OTHERWISE IN THE PLANS.

10. CONTRACTOR SHALL PROVIDE WATER AND OTHER MEASURES AS NECESSARY TO CONTROL DUST TO AN EXTENT ACCEPTABLE TO THE UNDERLYING PROPERTY OWNERS.

11. IN ACCORDANCE WITH THE COB DESIGN STANDARDS AND SPECIFICATIONS POLICY, A PRE-CONSTRUCTION MEETING SHALL BE SCHEDULED BY THE ENGINEER PRIOR TO BEGINNING CONSTRUCTION. THE CITY OF BOZEMAN, CONTRACTOR, ENGINEER, AND OTHER AFFECTED UTILITIES OR GOVERNMENT AGENCIES (IF APPLICABLE) SHALL BE PRESENT

12. ALL CONSTRUCTION MATERIALS THAT ARE INSTALLED ON THIS PROJECT MUST BE NEW.

13. SHOP/FABRICATION DRAWINGS WILL BE REQUIRED FOR ALL INSTALLED CONSTRUCTION MATERIALS. THEY MUST BE SUBMITTED BY THE CONTRACTOR TO THE ENGINEER PER THE PROCEDURES SET FORTH IN SPECIFICATIONS FOR REVIEW PRIOR TO THE PRE—CONSTRUCTION MEETING.

14. THE CONTRACTOR WILL BE RESPONSIBLE FOR PROVIDING AND MAINTAINING ALL NECESSARY PROJECT SITE ACCESS CONTROL DURING THE COURSE OF THE PROJECT.

15. THE CONTRACTOR WILL BE REQUIRED TO MAINTAIN A CLEAN JOB SITE.

16. THE CONTRACTOR WILL BE RESPONSIBLE FOR RESTORING THE GROUND SURFACE TO A PRE—PROJECT DISTURBANCE LEVEL INCLUDING BUT NOT LIMITED TO RESTORING VEGETATION, GROUND COVER, AND STREET AND SIDEWALK RESTORATION AND REPAIR.

17. REFER TO SPECIAL PROVISIONS FOR PERMITTING REQUIREMENTS.

18. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING AND MAINTAINING CONSTRUCTION SAFETY AND SANITATION FACILITIES.

19. ALL THRUST BLOCKING FOR WATER MAIN FITTINGS SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE CITY OF BOZEMAN STANDARD DRAWINGS # 02660-1 AND 02660-3.

20. ALL WATER MAINS MUST BE TESTED IN ACCORDANCE WITH MPWSS AND COB MODIFICATIONS PRIOR TO BEING PLACED INTO SERVICE.

21. CONTRACTOR SHALL PROVIDE ALL MATERIALS, EQUIPMENT AND FACILITIES REQUIRED FOR TESTING ALL UTILITY PIPING IN ACCORDANCE WITH MPWSS, MDEQ, AND COB SPECIFICATIONS. COST OF ALL INITIAL AND RETESTING SHALL BE BORNE BY THE CONTRACTOR.

22. THE CONTRACTOR SHALL PROVIDE A SET OF AS-BUILT DRAWINGS TO THE RPR PRIOR TO THE FINAL ACCEPTANCE.

23. WATER MAINS SHALL HAVE A MINIMUM OF 6.5—FT OF COVER. INSULATE OVER THE WATER MAINS WHERE MINIMUM COVER CANNOT BE MET.

AUX AUXILIARY

BENCHMARK BEGINNING POINT BEGIN VERTICAL CURVE

CL, © CMP COB CONC CENTERLINE CORRUGATED METAL PIPE CITY OF BOZEMAN CONCRETE COPPER DUCTILE IRON

DIAMETER DRAWING DWGS DRAWINGS

EACH EXISTING GRADE ELEV, EL EOP EST ELEVATION OF PAVEMENT **ESTIMATED** END VERTICAL CURVE

FDN FETS FLARED END TERMINAL SECTION FINISHED GRADE FIRE HYDRANT FG FHYD FL FLR FT FTG FLANGE FLOOR FEET FOOTING

GPM GALLONS PER MINUTE GATE VALVE

HORIZONTAL INVERT ELEVATION ΪΝV INVERT

LINEAR FEET

MATI MATERIAL MANUFACTURER MANHOLE MID POINT MINIMUM MECHANICAL JOINT MODIFICATIONS

MONTANA PUBLIC WORKS MONTAINA PUBLIC WORKS STANDARD SPECIFICATIONS
MONTAINA STATE UNIVERSITY
MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES MUTCD

NORTH

OFF OHP OVERHEAD POWER

POINT OF CURVATURE POINT OF INTERSECTION PROPERTY LINE POUNDS PER SQUARE INCH PSI PSIG POUNDS PER SQUARE INCH GAUGE POINT OF TANGENCY POLYVINYL CHLORIDE PVC PRV PRESSURE REDUCING VALVE

Q FLOW

REINFORCED CONCRETE PIPE REDUCER

ROW RPR RESIDENT PROJECT REPRESENTATIVE

SOUTH SCH SCHEDULE SD SECT STORM DRAIN SECTION SANITARY SEWER SANITARY SEWER MAN HOLE STA STANDARD TBM TBC TEMPORARY BENCHMARK

TOP BACK OF CURB TDH TOTAL DYNAMIC HEAD TEST PIT TOP OF WALL

UBC UPC UNIFORM BUILDING CODE UNIFORM PLUMBING CODE UNDERGROUND

VERT VERTICAL

WEST WITHOUT

ALLIED ENGINEERING SERVICES, INC.



MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406,994,5413 FAX: 406.994.5665

田 \triangleleft GR FIR

Ğ S **AMPU** HYDR

CONSTRUCTION

FOR

NOT

ALLIED

ELIMINARY DRAWN BY: FJF REVIEWED BY: RSR REV. DESCRIPTION DATE



PPA#22-0574 A/E#00-00-00 **AESI # 22-133**

SHEET TITLE C_{0.2}

SHEET **PROJECT NOTES &** GENERAL

INFORMATION



HYDRANT SUMMARY										
EX. HYDRANT #	BID PRIORITY	HYDRANT & AUX VALVE INFO	HYDRANT LEAD ESTIMATED EXISTING INVERT ELEVATION*	EXISTING GROUND ELEVATION AT HYDRANT BASE	FINISHED GRADE ELEVATION AT HYDRANT BASE	ESTIMATED EXISTING HYDRANT HEIGHT**	ANTICIPATED PROPOSED HYDRANT ASSEMBLY HEIGHT (CONTRACTOR TO VERIFY)	REPLACE:	RELOCATE?	RECOMMENDATIONS
13	ALTERNATE 3	COVERED BY BAG AUX VALVE PRESENT	4914.00	4921.51	MATCH EG	7.5'	7.5'	HYDRANT & AUX VALVE (POTENTIALLY HYDRANT LEAD AS WELL)		
22	ALTERNATE 1	AUX VALVE PRESENT	4887.45	4894.93	MATCH EG	7.5'	7.5'	HYDRANT & AUX VALVE	_	
27	ALTERNATE 1	AUX VAVLE PRESENT	4876.25	4884.53	MATCH EG	8.3'	8.5'	HYDRANT & AUX VALVE (POTENTIALLY HYDRANT LEAD AS WELL)	-	
53-	ALTERNATE 1	AUX VALVE PRESENT	4881.91	4888.18	MATCH EG	6.3'	6.5'	HYDRANT & AUX VALVE	_	
55	ALTERNATE 1	AUX VALVE PRESENT	4875.81	4882.57	MATCH EG	6.8'	7.0'	HYDRANT & AUX VALVE	_	
56	ALTERNATE 1	AUX VALVE NOT PRESENT DIRECTLY AT HYDRANT	4877.90	4883.44	.4883.95	5.5'	6.0'	HYDRANT & AUX VALVE	YES	
58	BASE BID	AUX VALVE NOT PRESENT DIRECTLY AT HYDRANT	4877.47	4883.10	.4883.80	5.6'	6.5'	HYDRANT & AUX VALVE	YES	
59	BASE BID	COVERED BY BAG AUX VALVE PRESENT	4874.65	4881.30	MATCH EG	6.6'	6.5'	HYDRANT & AUX VALVE	_	
61	BASE BID	COVERED BY BAG AUX VALVE PRESENT	4873.78	4880.47	MATCH EG	6.7'	7.0'	HYDRANT & AUX VALVE	-	
62	ALTERNATE 2	AUX VALVE PRESENT AUX VALVE NUT NOT ACCESSIBLE	4877.06	4881.22	4881.46	4.2'	4.5'***	HYDRANT & AUX VALVE	YES	POTHOLE 12" MAIN AT NEW HYDRANT LOCATION TO DETERMINE REPLACEMENT HYDRANT HEIGHT
63	ALTERNATE 2	AUX VALVE PRESENT	4874.01	4880.01	4880:04	6.0'	6.0'	HYDRANT & AUX VALVE	YES	
64	ALTERNATE 2	AUX VALVE PRESENT	4871.29	4878.02	MATCH EG	6.7'	7.0'	HYDRANT & AUX VALVE	_	
65	ALTERNATE 2	AUX VALVE PRESENT	4870.69	4876.41	4877.44	5.7'	7.0'	HYDRANT & AUX VALVE	YES	
68	BASE BID	COVERED BY BAG AUX VALVE BOX PRESENT AUX VALVE NUT NOT VISIBLE	4866.79	4873.74	MATCH EG	7.0'	7.0'***	HYDRANT & AUX VALVE	-	POTHOLE EXISTING HYDRANT LEAD TO DETERMINE REPLACEMENT HYDRANT HEIGHT
72	ALTERNATE 2	AUX VALVE BOX PRESENT AUX VALVE NUT NOT VISIBLE	4861.79	4866.02	MATCH EG	4.2'	4.5'***	HYDRANT & AUX VALVE	-	POTHOLE EXISTING HYDRANT LEAD TO DETERMINE REPLACEMENT HYDRANT HEIGHT
73	BASE BID	COVERED BY BAG AUX VALVE PRESENT	4861.42	4868.12	MATCH EG	6.7'	7.0'	HYDRANT & AUX VALVE		

- * EXISTING HYDRANT LEAD INVERTS WERE ESTIMATED BY SURVEYING ELEVATION OF TOP NUT OF AUX VALVES AT EACH HYDRANT. TOP NUT TO INVERT AT AUX VALVES ASSUMED TO BE 21". ALL HYDRANT LEADS ASSUMED TO BE 6" NOMINAL PIPE SIZE.
- ** ESTIMATED EXISTING HYDRANT HEIGHT DETERMINED BY CALCULATING THE DIFFERENCE BETWEEN THE ESTIMATED EXISTING HYDRANT LEAD INVERT AND THE EXISTING GROUND ELEVATION AT HYDRANT. EXISTING BURY LINES ON HYDRANTS WERE NOT SURVEYED.
- *** TOP NUT OF AUX VALVE WAS NOT ACCESSIBLE TO SURVEY AT THESE HYDRANTS. THEREFORE, THE ANTICIPATED PROPOSED HYDRANT ASSEMBLY HEIGHT IS VERY APPROXIMATE.

- 1. ALL EXISTING HYDRANT LEADS ASSUMED TO BE LEVEL (0% GRADE).
- 2. ALL EXISTING HYDRANT LEADS ASSUMED TO BE CAST IRON PER MSU RECORD DWGS. HOWEVER, MATERIAL MAY VARY.
- 3. EXISTING HYDRANT LEAD INVERTS WERE ESTIMATED BY SURVEYING ELEVATION OF TOP NUT OF AUX VALVES AT EACH HYDRANT.

 TOP NUT TO INVERT AT AUX VALVES ASSUMED TO BE 21". ALL HYDRANT LEADS ASSUMED TO BE 6" NOMINAL PIPE SIZE.

 3. CONTRACTOR TO COORDINATE WITH UTILITY COMPANIES REGARDING ALL UTILITY CROSSINGS AND ANY POTENTIAL UTILITY CONFLICTS.
- 4. ESTIMATED HYDRANT HEIGHT DETERMINED BY CALCULATING THE DIFFERENCE BETWEEN THE ESTIMATED HYDRANT LEAD INVERT AND THE EXISTING GROUND ELEVATION AT HYDRANT. EXISTING BURY LINES ON HYDRANTS WERE NOT SURVEYED.
- 5. ALL SECTIONS OF EXISTING WATER MAINS AT EXISTING HYDRANT TEES ASSUMED TO BE CAST IRON PER MSU RECORD DWGS UNLESS OTHERWISE NOTED (HYDRANTS 13, 22, 72, 73 HAVE VARYING MATERIAL AT EX. TEES PER MSU RECORD DWGS).
- 6. ALL TRENCHES FOR REPLACING HYDRANTS ASSUMED TO BE 4-FT WIDE.

- 1. UNDERGROUND UTILITIES NOT SHOWN IN PROFILE VIEWS.
- 2. UNDERGROUND UTILITIES SHOWN IN PLAN VIEWS MAY NOT BE ALL INCLUSIVE.

GENERAL NOTES:

- GATE VALVES NOT SHOWN IN PROFILE VIEWS.
- 2. AERIAL IMAGERY FROM 2021 CITY OF BOZEMAN.

- 1. REMOVE AND REPLACE ALL EXISTING HYDRANTS SHOWN ON SHEETS C2.1 THROUGH C2.6 (A TOTAL OF 16 HYDRANTS). SEE DETAIL 4/C4.1. INSTALL NEW AUX VALVE AND VALVE BOX AT EACH HYDRANT AS SHOWN IN DETAIL
- 2. FINISHED GRADE ELEVATIONS TO MATCH EXISTING GRADE WHEN BACKFILLING AND REPLACING CONCRETE AND ASPHALT.
- 3. SEE DETAIL 2/C4.1 FOR TRENCHING AND BACKFILL REQUIREMENTS.
- 4. CONTRACTOR TO VERIFY ELEVATIONS OF HYDRANT LEADS AND TO DETERMINE APPROPRIATE HYDRANT ASSEMBLY HEIGHT TO MATCH FG AT EACH LOCATION. BURY LINE OF NEW HYDRANTS TO MATCH FG OR EXTEND A MAXIMUM OF 5" ABOVE FG.
- 5. CONTRACTOR TO INSULATE HYDRANT LEADS IN ALL LOCATIONS WHERE 6.5' OF COVER IS NOT MET. INSULATION TYPE TO SATISFY COB MODS TO MPWSS IN SECTION 02660, 2.15.A. INSULATION TO BE INSTALLED PER DETAIL 3/C4.1.
- 6. CONTRACTOR TO VERIFY SIZES AND TYPES OF EXISTING FITTINGS AND PIPES, AND MAKE APPROPRIATE CONNECTIONS.

- 1. PROJECT SCHEDULE: AS NOTED IN THE TABLE ABOVE ON THIS SHEET, SOME HYDRANTS ARE HIGH PRIORITY THAN OTHERS. THE HYDRANTS NOTED AS HIGH PRIORITY SHOULD BE REPLACED FIRST. CONTRACTOR SHALL COORDINATE WITH MSU AND THE ENGINEER FOR TIMING OF HYDRANT REPLACEMENTS. THERE WILL BE SOME FLEXIBILITY FOR TIMING OF REPLACEMENTS.
- 2. CONSTRUCTION INSPECTION AND TESTING: CONSTRUCTION INSPECTION AND TESTING WILL BE PERFORMED BY AESI. THE ENGINEER SHALL BE NOTIFIED AT LEAST TWO DAYS PRIOR TO CONSTRUCTION IN ORDER TO PROVIDE INSPECTION. COORDINATE WITH MSU AND THE
- 3. TRAFFIC CONTROL: THE CONTRACTOR WILL BE RESPONSIBLE FOR PROVIDING AND MAINTAINING ALL NECESSARY TRAFFIC CONTROL DURING THE COURSE OF THE PROJECT. ALL ANTICIPATED TRAFFIC CONTROL MEASURES SHALL BE SUBMITTED BY THE CONTRACTOR TO THE PROJECT TEAM AND MUST BE APPROVED BY MSU AND THE PROJECT ENGINEER PRIOR TO ANY CONSTRUCTION ACTIVITY.
- 4. WATER MAIN MATERIAL; ZINC COATED PIPE WITH V-BIO ENHANCED POLYETHYLENE ENCASEMENT IS THE PREFERRED MATERIAL. COORDINATE WITH MSU AND THE ENGINEER FOR PRODUCT AVAILABILITY AND TIMING. IF NECESSARY DUE TO TIMING AND AVAILABILITY, STANDARD CLASS 51 DUCTILE IRON PIPE WITH V-BIO ENHANCED POLYETHYLENE ENCASEMENT MAY BE USED. ALL DUCTILE IRON PIPE AND FITTING ARE TO BE WRAPPED WITH V-BIO ENHANCED POLYTHENE.
- 7. EXPLORATORY EXCAVATION: ENGINEER RECOMMENDS USING A VAC TRUCK TO CONDUCTING EXPLORATORY EXCAVATION TO VERIFY LOCATIONS, ELEVATIONS, AND MATERIAL TYPES OF EXISTING HYDRANT LEADS PRIOR TO CONSTRUCTION. CONTRACTOR TO BACKFILL ANY HOLES OR TRENCHES FROM EXPLORATORY EXCAVATION.
- 8. IRRIGATION: COORDINATE WITH MSU FOR DAMAGE OR IMPACTS TO IRRIGATION LINES OR OTHER INFRASTRUCTURE.

SUBPARTS A&M, (ARM) 17.74 SUBCHAPTER 3: ASBESTOS CONTROL, AND (MCA) TITLE 75, PART 5.

- 9. <u>CONSTRUCTION STAKING</u>: CONTRACTOR TO COORDINATE WITH AESI FOR STAKING NEEDS. WE ANTICIPATE STAKES WILL BE PROVIDED FOR THE PROPOSED HYDRANT LOCATIONS AND FOR CONTROL. EXCESSIVE TRIPS REQUIRED DUE TO DISTURBED STAKES MAY BE AT THE COST
- 10. MAIN SHUT-DOWNS: ANTICIPATED GATE VALVE LOCATIONS TO BE USED FOR MAIN SHUT-DOWNS ARE SHOWN ON SHEETS C3.0 THROUGH C3.4. COORDINATE WITH MSU AND THE ENGINEER FOR FINAL SHUT-DOWN SECTIONS AND TIMING.
- 11. <u>PERMITS</u>; CONTRACTOR TO OBTAIN STREET CUT PERMITS THROUGH THE CITY OF BOZEMAN FOR ALL WORK WITHIN PUBLIC STREETS. GROUNDWATER DEWATERING MAY BE REQUIRED. CONTRACTOR TO OBTAIN GROUNDWATER DEWATERING PERMIT.
- 12. <u>BOLLARDS</u>: IN GENERAL, BOLLARDS ARE TO BE INSTALLED AT ALL HYDRANTS WHERE PRACTICAL. COORDINATE WITH MSU AND THE ENGINEER FOR FINAL BOLLARD CONFIGURATIONS.
- 13. <u>HYDRANT LEAD REPLACEMENT:</u> VERIFY CONDITION OF EXISTING HYDRANTS LEADS AND REPLACE AS NEEDED. COORDINATE WITH MSU AND THE ENGINEER. 14. HYDRANT LEAD ABANDONMENT: CONTRACTOR TO COORDINATE WITH MSU AND ENGINEER ON MEANS/METHODS OF ABANDONING EXISTING
- HYDRANT TEES AND/OR TAPPING VALVES. SEE DETAIL 1/C4.1. 15. <u>ASBESTOS CONCRETE PIPE</u>: IT IS POSSIBLE THAT AN EXISTING ASBESTOS CONCRETE PIPE MAY BE ENCOUNTERED FOR HYDRANT 13 OR OTHER LOCATIONS. IF THE LINE IS FOUND TO BE ASBESTOS CONCRETE IT SHALL BE REMOVED AND REPLACED. ALL ASBESTOS ABATEMENT WILL BE IN COMPLIANCE WITH MT DEQ RULES AND REGULATIONS INCLUDING BUT NOT LIMITED TO: (NESHAP) 40 CFR 61,

BASIS OF BEARING, COORDINATES
BEARINGS SHOWN ARE MONTANA STATE PLANE GRID.
DISTANCES ARE GROUND DISTANCES IN INTERNATIONAL FEET.

MONTANA COORDINATE SYSTEM NAD 83 HORIZONTAL DATUM: BOZEMAN CONTINUOUSLY OPERATING REFERENCE STATION PID DESIGNATION
DK7547 MTSU BOZEMAN CORS ARP

MONTANA STATE PLANE NAD 83(2011)(EPOCH: 2010.0000) NORTH LATITUDE 45'39'40.37689"
WEST LONGITUDE 111'02'42.00898"
UNITS: INTERNATIONAL FEET Convergence angle: -01°07'49"

DATUM NOTE: ELEVATIONS ARE BASED ON NAVD 88 VERTICAL DATUM

MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413 FAX: 406.994.5665

田 FIR 2 S AMPU

FOR CONSTRUCTION

NOT

ELIMINARY

ALLIED

DRAWN BY: EJF REVIEWED BY RSR REV. DESCRIPTION DATE




PPA#22-0574 A/E#00-00-00 **AESI # 22-133**

> SHEET TITLE C0.3

> > SHEET

EXISTING HYDRANT SUMMARY & NOTES





MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413 FAX: 406.994.5665

UPGRADE

CAMPUS FIRE PRELIMINARY - NOT FOR CONSTRUCTION

SEASON OF THE STATE O HYDRANT

REVIEWED BY: RSR REV. DESCRIPTION DATE



PPA#22-0574 A/E#00-00-00 AESI # 22-133

SHEET TITLE

C1.1


SHEET PROJECT OVERVIEW PLAN



ROTATE NEW HYDRANT TO FACE WES' (PERPENDICULAR TO SIDEWALK). ANTICIPATED EX. 6" WATER MAIN LOCATION (NOT SURVEYED) BASED ON MSU RECORD DRAWINGS X. HYDRANT 73 OVERED BY BAG EX. 6" WATER MAIN FROM UTILITY LOCATE PAINT) EX. 6" WATER MAIN MATERIAL TYPE UNKNOWN PER MSU RECORD DWGS


ROTATE NEW HYDRANT TO FACE WEST (PERPENDICULAR TO CURB LINE). LOCATION, DEPTH UNKNOWN STA: 0+05.6 X. HYDRANT 68 OVERED BY BAG AUX VALVE BOX PRESENT AUX VALVE NUT NOT VISIBLE STA: 0+23.00 EX. 6" WATER MAIN (FROM UTILITY LOCATE PAINT)

PLAN VIEW - HYDRANT 72 BID ALTERNATE #2




PROFILE VIEW - HYDRANT 72 BID ALTERNATE #2


PLAN VIEW - HYDRANT 73 BASE BID ITEM



PROFILE VIEW - HYDRANT 73 BASE BID ITEM



PLAN VIEW - HYDRANT 68 BASE BID ITEM



PROFILE VIEW - HYDRANT 68 BASE BID ITEM

MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413 FAX: 406.994.5665

PGRADE FIRE S

CAMPU HYDRANT

NOT FOR CONSTRUCTION DRAWN BY: EJF

DRAWN BY: EJF

REVIEWED BY: PSR

REVIEWED BY: RSR REV. DESCRIPTION DATE




PPA#22-0574


A/E#00-00-00 AESI # 22-133

SHEET TITLE

C2.1


SHEET PLAN & PROFILES: HYDRANTS 72, 73, 68








PLAN VIEW - HYDRANT 65 BID ALTERNATE #2




PROFILE VIEW - HYDRANT 65 BID ALTERNATE #2

PLAN VIEW - HYDRANT 64 BID ALTERNATE #2



PROFILE VIEW - HYDRANT 64 BID ALTERNATE #2

PLAN VIEW - HYDRANT 63 BID ALTERNATE #2



PROFILE VIEW - HYDRANT 63 BID ALTERNATE #2



MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413 FAX: 406.994.5665

PGRADE FIRE S

CAMPU HYDRANT

NOT FOR CONSTRUCTION

ALLIED


PRELIMINARY -DRAWN BY: EJF REVIEWED BY RSR REV. DESCRIPTION DATE




PPA#22-0574 A/E#00-00-00

AESI # 22-133 SHEET TITLE

SHEET PLAN & PROFILES: HYDRANTS 65, 64, 63











PLAN VIEW - HYDRANT 59 BASE BID ITEM




PROFILE VIEW - HYDRANT 59 BASE BID ITEM

PLAN VIEW - HYDRANT 55 BID ALTERNATE #1




PROFILE VIEW - HYDRANT 55 BID ALTERNATE #1

PLAN VIEW - HYDRANT 56 BID ALTERNATE #1



PROFILE VIEW - HYDRANT 56 BID ALTERNATE #1





MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413 FAX: 406.994.5665

PGRADE FIRE

S CAMPU HYDRANT

NOT FOR CONSTRUCTION

ALLIED

RELIMINARY DRAWN BY: EJF REVIEWED BY RSR REV. DESCRIPTION DATE




PPA#22-0574 A/E#00-00-00


AESI # 22-133


SHEET TITLE

C2.3


SHEET PLAN & PROFILES: HYDRANTS 59, 55, 56








PLAN VIEW - HYDRANT 61 BASE BID ITEM



PROFILE VIEW - HYDRANT 61 BASE BID ITEM


PLAN VIEW - HYDRANT 58 BASE BID ITEM



PROFILE VIEW - HYDRANT 58 BASE BID ITEM



PLAN VIEW - HYDRANT 62 BID ALTERNATE #2



PROFILE VIEW - HYDRANT 62 BID ALTERNATE #2

MONTANA STATE UNIVERSITY

MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413 FAX: 406.994.5665

S **PGRADE** FIRE S

NOT FOR CONSTRUCTION CAMPU HYDRANT

ALLIED

PRELIMINARY -DRAWN BY: EJF REVIEWED BY: RSR REV. DESCRIPTION DATE




PPA#22-0574 A/E#00-00-00


AESI # 22-133


SHEET TITLE

C2.4


SHEET PLAN & PROFILES: HYDRANTS 61, 58, 62







PLAN VIEW - HYDRANT 13 BID ALTERNATE #3




PROFILE VIEW - HYDRANT 13 BID ALTERNATE #3

NOTE:

ALL ASBESTOS ABATEMENT WILL BE IN COMPLIANCE WITH MT DEQ RULES AND REGULATIONS INCLUDING BUT NOT LIMITED TO: (NESHAP) 40 CFR 61, SUBPARTS A&M, (ARM) 17.74 SUBCHAPTER 3: ASBESTOS CONTROL, AND (MCA) TITLE 75, PART 5.


PLAN VIEW - HYDRANT 22 BID ALTERNATE #1



PROFILE VIEW - HYDRANT 22 BID ALTERNATE #1

) 10 20 30 SCALE (FEET)

PLAN VIEW - HYDRANT 53 BID ALTERNATE #1



PROFILE VIEW - HYDRANT 53 BID ALTERNATE #1



MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413 FAX: 406.994.5665

S FIRE UPGRADES

NOT FOR CONSTRUCTION

CAMPUS

HYDRANT U

DRAWN BY: EJF

REVIEWED BY: RSP

DRAWN BY: EJF
REVIEWED BY: RSR
REV. DESCRIPTION DATE




PPA#22-0574 A/E#00-00-00


AESI # 22-133 SHEET TITLE

C2.5

SHEET
PLAN & PROFILES:
HYDRANTS
13, 22, 53



PLAN VIEW - HYDRANT 27 BID ALTERNATE #1



PROFILE VIEW - HYDRANT 27 BID ALTERNATE #1





MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413 FAX: 406.994.5665

UPGRADE CAMPUS FIRE PRELIMINARY - NOT FOR CONSTRUCTION

ASSOCIATES BY THE STANDARY STA HYDRANT

REVIEWED BY: RSR REV. DESCRIPTION DATE



PPA#22-0574 A/E#00-00-00

AESI # 22-133 SHEET TITLE

C2.6

SHEET

PLAN & PROFILES: **HYDRANT 27**



ALL WATER SERVICE LINES SHOWN ARE ANTICIPATED LOCATIONS PER MSU RECORD DRAWINGS. ACTUAL LOCATIONS WILL VARY.



ANTICIPATED VALVE LOCATIONS AND ISOLATION PLAN. COORDINATE WITH MSU PRIOR TO CONSTRUCTION FOR ACTUAL MAIN SHUT-DOWNS AND ISOLATION VALVE OPERATION.



MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413

FAX: 406.994.5665

UPGRADE FIRE S

CAMPU HYDRANT

ALLIED

DRAWN BY: EJF REVIEWED BY RSR REV. DESCRIPTION DATE



PPA#22-0574 A/E#00-00-00 AESI # 22-133

SHEET TITLE

C3.1

SHEET ISOLATION PLAN: HYD: 55, 56, 58, 59, 61, 62, 63, 64, 65



WATER SERVICE LINE NOTE:

1. ALL WATER SERVICE LINES SHOWN ARE ANTICIPATED LOCATIONS PER MSU RECORD DRAWINGS. ACTUAL LOCATIONS WILL VARY.



NOTE:

ANTICIPATED VALVE LOCATIONS AND ISOLATION PLAN. COORDINATE WITH MSU PRIOR TO CONSTRUCTION FOR ACTUAL MAIN SHUT-DOWNS AND ISOLATION VALVE OPERATION.



MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413

FAX: 406.994.5665

PGRADE FIRE S CAMPU HYDRANT

ALLIED

DRAWN BY: EJF REVIEWED BY RSR REV. DESCRIPTION DATE



PPA#22-0574 A/E#00-00-00 **AESI # 22-133**

SHEET TITLE

C3.2

SHEET **ISOLATION PLAN:** HYDRANTS 68, 72, 73



MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413

FAX: 406.994.5665 S

UPGRADE CAMPUS FIRE

NOT FOR CONSTRUCTION HYDRANT PRELIMINARY -

DRAWN BY: EJF REVIEWED BY RSR REV. DESCRIPTION DATE



PPA#22-0574 A/E#00-00-00 AESI # 22-133

SHEET TITLE

C3.3


SHEET ISOLATION PLAN: **HYDRANTS** 22, 27, 53

DATE 11-17-2023

ANTICIPATED VALVE LOCATIONS AND ISOLATION PLAN. COORDINATE WITH MSU PRIOR TO CONSTRUCTION FOR ACTUAL MAIN SHUT-DOWNS AND ISOLATION VALVE OPERATION.

WATER SERVICE LINE NOTE:


ALL WATER SERVICE LINES SHOWN ARE ANTICIPATED LOCATIONS PER MSU RECORD DRAWINGS. ACTUAL LOCATIONS WILL VARY.





WATER SERVICE LINE NOTE:

ALL WATER SERVICE LINES SHOWN ARE ANTICIPATED LOCATIONS PER MSU RECORD DRAWINGS. ACTUAL LOCATIONS WILL VARY.



NOTE:

ANTICIPATED VALVE LOCATIONS AND ISOLATION PLAN. COORDINATE WITH MSU PRIOR TO CONSTRUCTION FOR ACTUAL MAIN SHUT-DOWNS AND ISOLATION VALVE OPERATION.



MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413 FAX: 406.994.5665

UPGRADE FIRE

S CAMPU HYDRANT

ALLIED

DRAWN BY: EJF REVIEWED BY: RSR REV. DESCRIPTION DATE



PPA#22-0574 A/E#00-00-00 **AESI # 22-133**


SHEET TITLE

C3.4 SHEET

ISOLATION PLAN: **HYDRANT 13**


- . IF EXISTING HYDRANT LEAD WAS INSTALLED WITH A TAPPING VALVE INSTEAD OF A TEE, USE APPROPRIATE METHODS AND MATERIALS TO ABANDON THE TAPPING VALVE. DISCUSS WITH ENGINEER AND CONFIRM WITH WATER DEPARTMENT BEFORE IMPLEMENTING.
- IF A DUCTILE IRON CAP CANNOT BE USED TO ABANDON EXISTING HYDRANT TEE, DISCUSS WITH ENGINEER AND WATER DEPARTMENT BEFORE MOVING FORWARD WITH ABANDONMENT. MODIFICATIONS TO EXISTING MAIN MAY BE NECESSARY WITH TRANSITION FITTINGS AND/OR SOLID SLEEVE COUPLINGS.






- 1. THIS DETAIL APPLIES TO ALL UNDERGROUND WATER LINES.
- 2. INSULATION BOARD SHALL BE INSTALLED ABOVE THE PIPE WHEREVER ANY WATER DISTRIBUTION PIPING (INCLUDING MAINS, SERVICES, AND FIRE HYDRANT LEADS) HAS LESS THAN 6.5' OF COVER. SEE PIPE INSULATION DETAIL 2/C4.1 FOR LOCATION AND WIDTH REQUIREMENTS.
- 3. WHERE TRENCH PASSES THROUGH EXISTING PAVEMENT THE PAVEMENT SHALL BE CUT ALONG A NEAT VERTICAL LINE A MINIMUM OF 12" FROM THE EDGE OF THE TRENCH OPENING. WHERE NEAT LINE IS LESS THAN 3' FROM EDGE OF EXISTING PAVEMENT OR CURB AND GUTTER SECTION, REMOVE AND REPLACE ENTIRE PAVEMENT SECTION BETWEEN TRENCH AND EDGE OF PAVEMENT.





STANDARD INSULATION CONFIGURATION



NOTE: A+2B > REQUIRED INSULATION WIDTH WHERE A = TRENCH WIDTH


GRANULAR FILL

ALTERNATE INSULATION CONFIGURATION

INSULATION MININ	INSULATION MINIMUM REQUIREMENTS TABLE							
DEPTH OF BACKFILL OVER PIPE	INSULATION THICKNESS	INSULATION WIDTH*						
2'-0"	4.0"	8'						
3'-0"	4.0"	6'						
4'-0"	2.0"	4'						
5'-0"	2.0"	2'						
6'-0"	2.0"	2'						

* ACTUAL MINIMUM INSULATION WIDTH TO BE INSTALLED IS THE GREATER OF TRENCH WIDTH OR CALCULATED INSULATION WIDTH LISTED IN TABLE ABOVE.





NOTE:

- 1. ALL HYDRANTS TO HAVE BOLLARDS INSTALLED PER DETAIL 4/C4.2.
- 2. THRUST BLOCKS MAY BE NECESSARY AT HYDRANTS IF MECHANICAL JOINT RESTRAINTS CANNOT BE PROPERLY FITTED TO EXISTING HYDRANT TEES OR TAPPING VALVES.





MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413

FAX: 406.994.5665 DE PGR

FIR S CONSTRUCTION CAMPU HYDRA

FOR

NOT

ALLIED

ELIMINARY DRAWN BY EJF REVIEWED BY: RSR REV. DESCRIPTION DATE



PPA#22-0574 A/E#00-00-00 AESI # 22-133

> SHEET TITLE C4.1

> > SHEET

DETAILS

	STANDARD DIMENSIONS FOR THRUST BLOCKING									
FITTING	TEES &	PLUGS	90. 1	BEND	45° BEND	& WYES	RED. & 22.5° BEND			
SIZES	Α	В	Α	В	Α	В	Α	В		
4"	1'-7"	1'-2"	1'-9"	1'-6"	1'-8"	0'-10"	1'-7"	0'-6"		
6"	2'-0"	1'-11"	2'-5"	2'-2"	1'-10"	1'-7"	1'-9"	0'-10"		
8"	2'-8"	2'-6"	3'-2"	3'-0"	2'-5"	2'-1"	1'-9"	1'-6"		
10"	3'-4"	3'-3"	4'-0"	3'-10"	3'-0"	2'-9"	2'-2"	1'-11"		
12"	4'-0"	3'-10"	4'-8"	4'-8"	3'-8"	3'-3"	2'-7"	2'-3"		
14"	5'-5"	3'-10"	6'-6"	4'-11"	4'-9"	3'-5"	3'-5"	2'-5"		


TEE (PLUGGED)

BEND

TEE

- SOME LOCATIONS MAY REQUIRE CONCRETE THRUST BLOCKS TO BE INSTALLED BECAUSE MECHANICAL JOINT RESTRAINTS MIGHT NOT BE COMPATIBLE WITH EXISTING FITTINGS AND/OR EXISTING PIPE MATERIAL.
- THE USE OF MEGA-LUG JOINT RESTRAINTS ARE RECOMMENDED AT ALL VALVES, FITTINGS, AND HYDRANTS. THRUST BLOCKING IS OPTIONAL AT EACH LOCATION WHERE MEGA-LUG JOINT RESTRAINTS ARE PROPERLY USED.
- 3. THIS TABLE IS BASED ON 150 PSI MAIN PRESSURE AND 2000 PSF SOIL BEARING PRESSURE.
- 4. WRAP ALL FITTINGS WITH POLYETHYLENE ENCASEMENT.






NOTE:


1. SAW CUT SIDEWALKS ALONG EXISTING JOINTS.





PAINT POSTS WITH SHERWIN-WILLIAMS METALATEX SEMI-GLOSS COATING, SAFETY RED (B42 R38 620-4069).





NOTES:

- MATCH EXISTING CURB & GUTTER PROFILE GEOMETRY. THE EXISTING GEOMETRY WILL LIKELY MATCH THE CITY OF BOZEMAN STANDARD SHOWN ABOVE.
- 2. SAW CUT CURB & GUTTER PERPENDICULAR TO FACE OF CURB.
- 3. SUBGRADE OR BASE COURSE COMPACTION SHALL CONFORM TO SECTION 02230 (M.P.W. SPECS.)
- 4. CONTRACTION JOINTS SHALL BE PLACED AT 10' INTERVALS AND SHALL HAVE A MINIMUM DEPTH OF 3/4" AND MINIMUM
- 5. 1/2" EXPANSION JOINT MATERIAL SHALL BE PLACED AT ALL P.C.S, P.T.S, CURB RETURNS AND AT NOT MORE THAN 300' INTERVALS. THE EXPANSION MATERIAL SHALL EXTEND THROUGH THE FULL DEPTH OF THE CURB & GUTTER.
- 6. CONCRETE SHALL BE CLASS M-4000.
- 7. CRUSHED GRAVEL BASE SHALL MEET THE REQUIREMENTS OF SECTION 02235 (MPW SPECS.) FOR CURB AND GUTTER REPLACEMENT PROJECTS, WASHED ROCK MAY BE USED FOR THE GRAVEL BASE.





MSU-CPDC

MONTANA STATE UNIVERSITY BOZEMAN, MONTANA PHONE: 406.994.5413

FAX: 406.994.5665 **PGRADE** FIRE

CAMPUS PRELIMINARY - NOT FOR CONSTRUCTION HYDRANT

ALLIED

DRAWN BY: EJF REVIEWED BY RSR REV. DESCRIPTION DATE



PPA#22-0574 A/E#00-00-00

AESI # 22-133

SHEET TITLE

C4.2 SHEET

DETAILS